



# HYTAC<sup>®</sup> Standard Size Chart



HYTAC materials are available in a wide range of standard and custom sizes.

		HYTAC-W, WF, WFT, FLX, FLXT, C1R													
		Standard Stock Sizes								Made to order					
Standard Rod Diameter:	in	2.0	2.5	3.0	3.5	4.0	4.5	5.0	6.0	7.0	8.0	9.0	9.5	10.0	12.0
	mm	51	64	76	89	102	114	127	152	178	203	229	241	254	305
12" (305mm) Length											•	•	•	•	•
24" (610mm) Length		•	•	•	•	•	•	•	•	•					

		HYTAC-W, WF, WFT, FLX, FLXT, C1R									
		Standard Stock Sizes								Made to order	
Standard Sheet Thickness:	in	1.0	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	6.0
	mm	25	38	51	64	76	89	102	114	127	152
24" (610 mm) W x 26" (660mm) L		•	•	•	•	•	•	•	•		•
24" (610 mm) W x 60" (1524mm) L		•	•	•	•	•	•	•	•	•	•

60" /1524mm: made to order

		HYTAC B1X* & XTL										
		Standard Stock Sizes								Made to order		
Standard Rod Diameter:	in	2.0	2.5	3.0	3.5	4.0	4.5	5.0	6.0	7.0	8.0	10.0
	mm	51	64	76	89	102	114	127	152	178	203	254
24" (610mm) Length		•	•	•	•	•	•	•	•	•	•	•

		HYTAC B1X* & XTL								
		Standard Stock Sizes								Made to order
Standard Sheet Thickness:	in	1.0	1.5	2.0	2.5	3.0	3.5	4.0	4.5	6.0
	mm	25	38	51	64	76	89	102	114	152
24" (610mm) W x 24" (610mm) L		•	•	•	•	•	•	•	•	•
24" (610mm) W x 48" (1219mm) L		•	•	•	•	•	•	•	•	

Custom-cast or custom-cut sizing available - contact CMT with requirements

**Note:** HYTAC-W, WF, WFT, FLX, FLXT and C1R standard stock tolerances are + 0%, - 1.5% of thickness or diameter HYTAC-XTL, B1X tolerances are + .187" (5mm), - 0.0" (0mm) of thickness or diameter.

CUSTOM CUT tolerances are +.125" (3mm), - 0.0" (0mm) CUSTOM CAST tolerances are specified based upon tooling design.