



## HYTAC® Standard Size Chart

HYTAC materials are available in a wide range of standard and custom sizes.

		Standard Stock Sizes									Made to order						
HYTAC-W, WF, WFT, FLX, FLXT, C1R	<b>Standard Rod Diameter:</b>	in	2.0	2.5	3.0	3.5	4.0	4.5	5.0	6.0	7.0	8.0	9.0	9.5	10.0	12.0	
		mm	51	64	76	89	102	114	127	152	178	203	229	241	254	305	
		12" (305mm) Length										●	●	●	●	●	
		24" (610mm) Length	●	●	●	●	●	●	●	●	●	●					
		<b>Standard Sheet Thickness:</b>	in	1.0	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	6.0				
			mm	25	38	51	64	76	89	102	114	127	152				
		24" (610 mm) W x 26" (660mm)	L	●	●	●	●	●	●	●	●		●				
		24" (610 mm) W x 60" (1524mm)	L	●	●	●	●	●		●		●	●	60" /1524mm: made to order			
				Standard Stock Sizes									Made to order				
	HYTAC B1X & XTL*	<b>Standard Rod Diameter:</b>	in	2.0	2.5	3.0	3.5	4.0	4.5	5.0	6.0	7.0	8.0	10.0			
		mm	51	64	76	89	102	114	127	152	178	203	254				
		12" (305mm) Length	●														
		24" (610mm) Length	●	●	●	●	●	●	●	●	●	●	●				
		<b>Standard Sheet Thickness:</b>	in	1.0	1.5	2.0	2.5	3.0	3.5	4.0	4.5	6.0					
			mm	25	38	51	64	76	89	102	114	152					
	24" (610mm) W x 24" (610mm)	L	●	●	●	●	●	●	●	●	●						
	24" (610mm) W x 48" (1219mm)	L	●	●	●	●	●	●									

**Custom-cast or custom-cut sizing available. Contact CMT with requirements.**

Note HYTAC-W, W F, WFT, FLX, FLXT and C1R standard stock tolerances are + 0%, - 1.5% of thickness or diameter.

\*HYTAC-XTL & B1X tolerances are + .187" (5mm), -0.0" (0mm) of thickness or diameter. Length and width tolerances are +/- 0.25" (6.35mm) for all materials.

CUSTOM CUT tolerances are +.125" (2mm), -0.0" (0mm). CUSTOM CAST tolerances are specified based upon tooling design.